

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 December 2004 (16.12.2004)

PCT

(10) International Publication Number
WO 2004/109114 A1

(51) International Patent Classification⁷: **F04C 29/10**,
15/04, F04B 39/00

(21) International Application Number:
PCT/KR2004/001028

(22) International Filing Date: 3 May 2004 (03.05.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10-2003-0037662 11 June 2003 (11.06.2003) KR

(71) Applicant (for all designated States except US): **LG ELECTRONICS INC.** [KR/KR]; 20, Yoido-dong, Youngdungpo-gu, Seoul 150-721 (KR).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BAE, Ji Young** [KR/KR]; Yongho 2- dong, 521-18, Nam-gu, Busan


608-767 (KR). **PARK, Kyoung Jun** [KR/KR]; H-210, LG Electronics Dormitory, Gaumjung-dong, Changwon-si, Gyeongsangnam-do 641-711 (KR). **JANG, Chang Yong** [KR/KR]; Bulim APT., 101-1005, Maegok-dong, Buk-gu, Gwangju-si 500-815 (KR). **KIM, Hyeon** [KR/KR]; Daewoo APT., 201-303, Namsan-dong, Changwon-shi, Gyeongsangnam-do 641-090 (KR).

(74) Agents: **BAHNG, Hae Cheol** et al.; Kims International Patent & Law Office, 15th Floor Yo Sam Building, 648-23, Yeoksam-dong, Kangnam-gu, Seoul 135-080 (KR).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

[Continued on next page]

(54) Title: **ROTARY COMPRESSOR**



(57) Abstract: Disclosed is a rotary compressor having two compression capacities in clockwise and counterclockwise directions. The present invention provides a rotary compressor comprising: a driving shaft (13) being rotatable clockwise and counterclockwise, and having an eccentric portion (13a) of a predetermined size; a cylinder (21) having a predetermined inner volume; a roller (22) installed rotatably on an outer circumference of the eccentric portion (13a) so as to contact an inner circumference of the cylinder (21), performing a rolling motion along the inner circumference and forming a fluid chamber (29) to suck and compress fluid along with the inner circumference; a vane (23) installed elastically in the cylinder (21) to contact the roller (22); upper and lower bearings (24, 25) installed respectively in upper and lower portions of the cylinder (21), for rotatably supporting the driving shaft (13) and hermetically sealing the inner volume; suction (27) and discharge ports (26) communicating with the fluid chamber (29) so as to suck and discharge the fluid; a suction plenum (500) communicating with the suction ports (27) and preliminarily storing the fluid; and a compression mechanism configured to form different sizes of compressive spaces in the fluid chamber (29) depending on the rotational direction of the driving shaft (13).

WO 2004/109114 A1



(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*